


Modular Kit Product Selection

Base Contactor – NEMA Sizes 0...4⁽¹⁾

NEMA Size	Continuous Ampere Rating [A]	Maximum Horsepower Rating (Full Load Current Must Not Exceed Continuous Ampere Rating)						600V AC Maximum, 60 Hz		
		1-Phase Motor Voltage ⁽²⁾		3-Phase Motor Voltage				3 Power Poles	4 Power Poles	5 Power Poles
		115V	230V	200V	230V	50 Hz		Cat. No. ⁽³⁾	Cat. No. ⁽³⁾	Cat. No. ⁽³⁾
						380...415V	460...575V			
00	9	0.33	1	1.5	1.5	2	2	(4)	(4)	—
0	18	1	2	3	3	5	5	500-A0@930	500-A0@940	500-A0@950
1	27	2	3	7.5	7.5	10	10	500-B0@930	500-B0@940	500-B0@950
2	45	3	7.5	10	15	25	25	500-C0@930	500-C0@940	500-C0@950
3	90	7.5	15	25	30	50	50	500-D0@930	500-D0@940	500-D0@950
4	135	—	—	40	50	75	100	500-E0@930	500-E0@940	500-E0@950
5	270	—	—	75	100	150	200	(4)	(4)	—

- (1) Includes a 120V AC coil and one N.O. auxiliary contact, as standard.
 (2) NEMA sizes 0...3 can be wired for 3-phase or 1-phase applications, but 1-phase coil codes are no longer valid.
 (3) The cat. nos. as listed are incomplete. Select a value from the Voltage Code table to complete each cat. no.
 Example: To select a 120V AC coil voltage, Cat. No. 500-A0@940 becomes Cat. No. 500-A0@940.
 (4) See NEMA Sizes 00 and 5 on page 8.

⚡ Voltage Code

Note: The base contactor includes a 120V AC coil as standard. For all other voltages, an alternate coil will be included in the modular kit for field installation.

[V]	24	110	120	125	208	220	240	250	277	380	415	440	480	550	600
AC, 50 Hz	J	D	—	—	—	—	—	—	—	—	—	—	—	—	—
AC, 60 Hz	J	—	D	—	H	—	A	—	F	—	—	—	B	—	C
DC ⁽¹⁾	VL	—	—	VG	—	—	—	VG	—	—	—	—	—	—	—

- (1) DC coil voltages are only available for NEMA sizes 0...3. When ordering a DC coil voltage, add "DC" to the catalog number.
 Example: 500DC-B0VL-930.

Modular Kit Options

Options	
Code	Description
17	Surge suppressor for 120 or 240V AC coil
9d ⁽¹⁾	One N.O. auxiliary contact
9n ⁽¹⁾	One N.C. auxiliary contact

- (1) Up to six combinations of auxiliary contacts can be selected. For example, Code 90011 indicates two N.O. contacts and two N.C. contacts.

Example: Catalog Number 500-C0@930-17-90 includes a NEMA size 2, 3-pole contactor with a 120V AC coil, a surge suppressor, and one N.O. auxiliary contact.